


PORTLAND

CCT selectable IP54 decorative LED bulkhead fitting for commercial indoor areas



CCT SELECTABLE
4000K/5000K



AVAILABLE WITH MICRO-WAVE
SENSOR FITTED



APPLICATIONS

- For commercial interior use in corridors, stairs, toilets and changing rooms

CONSTRUCTION

- Polycarbonate base and bezel
- Micro-prismatic polycarbonate controller
- Available with either a White bezel (WH) or Chrome bezel (CH), as listed

TECHNICAL DETAILS

- Two wattages available:
 - 15W, 1,270 lm, 85 l.lm/c.W
 - 18W, 1,610 lm, 89 l.lm/c.W
- CRI >80
- CCT selectable 4000K/5000K
- ENEC approved, flicker free, LED driver
- Emergency maintained 3 hours versions (suffix M3) available, as listed

TECHNICAL DETAILS (contd.)

DIMMING Dim-to-10% (Corridor Function) available on all variants. Suffix CF. As listed

SENSOR Available with built in micro-wave sensor. Suffix MW. As listed

DIMMING & SENSOR A popular combination is corridor function & micro-wave sensor. Suffix CFMW. As listed

ORDER CODE	DESCRIPTION
NPO15/WH/O/840-850	Portland 15W LED IP54 White Opal 840-850
NPO15/WH/O/M3/840-850	Portland 15W LED IP54 White Opal M3 840-850
NPO18/WH/O/840-850	Portland 18W LED IP54 White Opal 840-850
NPO18/WH/O/M3/840-850	Portland 18W LED IP54 White Opal M3 840-850
NPO15/CH/O/840-850	Portland 15W LED IP54 Chrome Opal 840-850
NPO15/CH/O/M3/840-850	Portland 15W LED IP54 Chrome Opal M3 840-850
NPO18/CH/O/840-850	Portland 18W LED IP54 Chrome Opal 840-850
NPO18/CH/O/M3/840-850	Portland 18W LED IP54 Chrome Opal M3 840-850
NPO15/CF/MW/WH/O/840-850	Portland 15W LED IP54 White Opal CF MW 840-850
NPO15/CF/MW/WH/O/M3/840-850	Portland 15W LED IP54 White Opal CF MW M3 840-850
NPO15/WH/O/MW/840-850	Portland 15W LED IP54 White Opal MW 840-850
NPO15/WH/O/MW/M3/840-850	Portland 15W LED IP54 White Opal MW M3 840-850
NPO18/WH/O/MW/840-850	Portland 18W LED IP54 White Opal MW 840-850
NPO18/WH/O/MW/M3/840-850	Portland 18W LED IP54 White Opal MW M3 840-850

